

SlipNOT® perforated plate continually provides drainage and slip resistance for applications that are completely submerged in oils, water, grease, fats, or any other slick additive. Perforated plate also allows for light and airflow.

PRODUCT INFORMATION

Thicknesses: 1/8", 3/16", 1/4"

Stock sizes:

4'x8'	5'x8'
4'x10'	5'x10'
4'x12'	5'x12'

*Custom sizes can be fabricated to meet job specifications

Patterns (a wide variety of hole patterns and options available)

- ▶ 1/4" diameter on 3/8" diameter centers (galvanized steel not available)
- ➤ 3/8" diameter on 9/16" staggered centers
- ▶ 1/2" diameter on 11/16" staggered centers
- ▶ 9/16" diameter on 3/4" staggered centers
- Customer specified

Standard minimum margins or customer specific

Available SlipNOT® surfaces: Steel, Stainless Steel, and Aluminum

SlipNOT® finishes: Mill, Painted, or Galvanized Steel

Available in: Grade 1 (Fine), Grade 2 (Medium), or Grade 3 (Coarse - steel surface only) **Installation method:** Welded or fastened to existing structures or to framing supports

Note: Perforation removes about 2/3 of the strength of the plates. Additional supports may be required.

Advantages

- ► Allows for drainage, light, and air passage
- ► Retrofits over existing structures with minimum effort
- ► Flexes when walked on to prevent worker fatigue

