

# PLATE STAIR TREADS

*SlipNOT®* plate stair treads are for areas where full surface coverage is required to ensure a safe walking and working surface. Plate stair treads can be used in new construction or can be retrofitted over existing slippery stairs.

## PRODUCT INFORMATION

**Thicknesses:** 1/8", 3/16", 1/4"

**Widths:** 10 -12 inches (typical), or as specified

**Lengths:** up to 10'

**Nosing depth:** 1-1/4" – 2" (typical), or as specified

**Riser:** up to 7", or as specified

**Bend degree:** 82, 90, or to degree angle specified

**Styles:** L shaped, C shaped, or Z shaped

***SlipNOT®* finishes:** Mill, Painted, or Hot-Dipped Galvanized (3/16" minimum thickness)

**Plate stair treads are available in:** Grade 1 (Fine), Grade 2 (Medium), and Grade 3 (Coarse - Steel surface only)

**Typical alloys** (other alloys available)

Steel	A-36	CQ
Stainless Steel	304	316
Aluminum	5052	3003

**Installation method:** Countersunk holes for fastening to supports, weld to existing metal structures or framing, and standard end plates or carrier angles may be added

## Advantages

- ▶ Solid surface provides maximum surface area for greatest traction
- ▶ Easily installed in new construction or retrofitted over existing treads

