

SPECIFY SLIPNOT

Or tell us, why not?

Our proprietary technology, a multi-step engineered surface preparation and modification process, transforms hazardous spaces into environments where people can move faster, be confident in their workspaces, and stop worrying about lost time from slips and falls.



THE SLIPNOT DIFFERENCE

PERFORMANCE TECHNOLOGY



Durability 4,000 PSI

Strength to withstand the toughest environments & demanding foot-traffic



Longevity Rockwell C 55

6x harder than the surface applied to resulting in the potential to last decades



Grit-Free Debris-Free Process

Grit is dangerous for individuals health, hazardous to machinery, and can pollute end-products



Regular Testing FDA compliant

Exceeds all COF regulatory requirements, including OSHA & ADA

Don't look at cost alone.

Consider a holistic approach of a project to understand true life-cycle costs



Replacements costs

Temporary solutions require frequent upkeep and replacement

Reduced productivity

People move differently due to lack of confidence in work area

Expensive injury claims

The cost of 1 slip and fall incident can be significant



Schedule a free lunch & learn

Make SLIPNOT the standard for all your specifications

All SLIPNOT products are manufactured in the USA and can be customized to your surface design and installation requirements. Our team of experts are available to create a worry-free education, selection, and delivery experience.

IDENTIFY ALLOY

The longevity and performance of SLIPNOT depends on selecting the appropriate alloy for the environment.

STEEL

Extremely versatile. Requires proper protection in outdoor applications or areas where water and moisture may be present. Galvanization will help protect against rust and corrosion that may form in those environments.

- Durable
- Cost-Effective

Available Grades: Grade 1, Grade 2, Grade 3

STAINLESS STEEL

From food & beverage to aerospace our stainless steel products provide optimum durability, natural chemical and corrosion resistance, and are aesthetically pleasing to fit nearly any project.

- NFSI Certified HIGH-TRACTION
- NSF Certified

Available Grades: Grade 1, Grade 2

ALUMINUM

Aluminum is the ideal choice for projects that require a lightweight material and where rust and corrosion is a concern

- High strength-to-weight ratio
- Easily fabricated

Available Grades: Grade 1, Grade 2

SELECT SURFACE GRADE

Our high traction surface is a series of peaks and valleys. Our grades refer to the approximate added profile height of the SLIPNOT application.



DOCUMENT KEY DIFFERENTIATORS

Our proprietary technology creates a set of unique characteristics that if included in spec, do not allow for deviation from SLIPNOT.

	Steel	Stainless*	Aluminum
Surface Hardness	55+ Rockwell "C"	55+ Rockwell "C"	N/A
Minimum Bond Strength	Over 3,500psi	Over 3,500psi	Over 1,500psi
Minimum (Wet) COF	0.8	0.8	0.8

*Additional key differentiator: certified HIGH-TRACTION by the NFSI

GENERATE YOUR SLIPNOT SPECIFICATION

Indicate the Product
(Treads, Plate, Grate, Plank, Etc.)

1

Choose Grade
(Grade 1, Grade 2, or Grade 3)

2

Identify Alloy
(Steel, Stainless, Aluminum)

3

Include SLIPNOT Key
Differentiators

4

Spec Example:

Stair tread surface shall incorporate SLIPNOT high-traction **Stainless Steel - Grade 2**, with **bond strength exceeding 3,500psi** and **surface hardness exceeding 55 Rockwell "C" Scale**, **minimum COF of 0.8 (wet)**, and **certified HIGH-TRACTION by the NFSI**



For More Details:

**CONSTRUCTION
SPECIFICATION INSTITUTE
SLIPNOT 3-PART**

